



DECLARATION OF PERFORMANCE

as required by Regulation (EU) No. 305/2011
and amendment of Annex III, (EU) No. 574/2014

No. DoP: 1410002003.Rev.01

1. *Unique identification code of the product-type:* **SILACRYL** (See Product Packaging)
2. *Intended use(es):* Sealants for façade elements - EN 15651-1: F-EXT-INT
3. *Manufacturer:* VITEX S.A ,P.O. Box 139 IMEROS TOPOS ,
19 300 ASPROPYRGOS, GREECE
4. *Authorised representative:* Not Applicable
5. *System(s) AVCP of assessment and verification of constancy of performance:* System 3
System 3 for reaction to fire
6. *a. Harmonized Standard:* EN 15651-1
Notified Bodies : The notified body SKZ – TeConA GmbH (1213) performed the initial type testing according to EN 15651-1 and reaction to fire under system 3 and issued a test report.
7. *Declared Rerformance*
Conditioning: Procedure A according to ISO 8339)
Substrate: Mortar M2 (without primer)

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONISED TECHNICAL SPECIFICATION
Reaction to fire	Class E	EN 15651-1:2012
Release of chemicals dangerous to the environment and health	NPD (*)	
Water tightness and air tightness		
<i>Resistance to flow</i>	≤ 3 mm	
<i>Loss of volume</i>	≤ 45 %	
<i>Tensile properties at break at 23°C</i>	≥ 25%	
<i>Tensile properties after immersion to water at 23°C</i>	≥ 25%	
Durability	Pass	

(*) See material safety data sheet
NPD: No Performance Determined
NF: No Failure

8. *Appropriate Technical Documentation and/or Specific Technical Documentation:* Not Applicable


The performance of the product identified above is in conformity with the set of declared performance. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

PLACE/ DATE

Aspropyrgos Attica, 15.06.2021

QEHS Manager



Ioulia Antonakopoulou