



# VITEX S.A.

## ACRYLIC PRIMER

Revision nr.8  
Dated 02/07/2024  
Printed on 02/09/2024  
Page n. 1 / 10  
Replaced revision:7 (Dated 10/05/2022)

EN

## Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name **ACRYLIC PRIMER**

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **Acrylic waterbased primer**

#### 1.3. Details of the supplier of the safety data sheet

Name **VITEX S.A.**  
Full address **IMEROS TOPOS**  
District and Country **19300 ASPROPYRGOS (ATTIKI)**  
**GREECE**  
Tel. **(0030) 2105589400**  
Fax **(0030) 2105597859**

e-mail address of the competent person responsible for the Safety Data Sheet **vitexlab@vitex.gr**

Supplier: **VITEX S.A**

#### 1.4. Emergency telephone number

For urgent inquiries refer to **(0030) 2105589400**  
**(0030) 2107793777 Emergency number Greece 24/7**  
**1401 Cyprus**

### SECTION 2. Hazards identification

#### 2.1. Classification of the substance or mixture

The product is not classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP). However, since the product contains hazardous substances in concentrations such as to be declared in section no. 3, it requires a safety data sheet with appropriate information, compliant to (EU) Regulation 2020/878.

Hazard classification and indication: --

#### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms: --

Signal words: --

Hazard statements:

**EUH210** Safety data sheet available on request.  
**EUH208** Contains: 5-Chloro-2-methyl- 3(2H)-isothiazolone mixture with 2-Methyl- 3(2H)-isothiazolone (3:1)  
2-methyl-2H-isothiazol-3-one  
1,2-benzisothiazol-3(2H)-one  
May produce an allergic reaction.

Precautionary statements:

**P102** Keep out of reach of children.  
**P333+P313** If skin irritation or rash occurs: Get medical advice / attention.  
**P273** Avoid release to the environment.  
**P301+P312** IF SWALLOWED: Call a POISON CENTER / doctor / . . . / if you feel unwell.



# VITEX S.A.

## ACRYLIC PRIMER

Revision nr.8  
Dated 02/07/2024  
Printed on 02/09/2024  
Page n. 2 / 10  
Replaced revision:7 (Dated 10/05/2022)

EN

### SECTION 2. Hazards identification ... / >>

VOC (Directive 2004/42/EC) :

Primers.

VOC given in g/litre of product in a ready-to-use condition : 6,00  
Limit value: 30,00

#### 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration  $\geq$  0.1%.

### SECTION 3. Composition/information on ingredients

#### 3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
<b>1,2-benzisothiazol-3(2H)-one</b> INDEX 613-088-00-6	$0 < x < 0,0359$	<b>Acute Tox. 2 H330, Acute Tox. 4 H302, Eye Dam. 1 H318, Skin Irrit. 2 H315, Skin Sens. 1A H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1</b> <b>Skin Sens. 1A H317: <math>\geq 0,036\%</math></b> <b>ATE Oral: 500 mg/kg, ATE Inhalation vapours: 0,501 mg/l</b>
EC 220-120-9 CAS 2634-33-5		
<b>2-methyl-2H-isothiazol-3-one</b> INDEX	$0 < x < 0,00149$	<b>Acute Tox. 2 H330, Acute Tox. 3 H301, Acute Tox. 3 H311, Skin Corr. 1B H314, Eye Dam. 1 H318, Skin Sens. 1A H317, Aquatic Acute 1 H400 M=10, Aquatic Chronic 1 H410 M=1, EUH071</b> <b>Skin Sens. 1A H317: <math>\geq 0,0015\%</math></b> <b>ATE Oral: 100 mg/kg, ATE Dermal: 300 mg/kg, ATE Inhalation vapours: 0,501 mg/l, ATE Inhalation mists/powders: 0,051 mg/l</b>
EC 220-239-6 CAS 2682-20-4		
<b>5-Chloro-2-methyl- 3(2H)-isothiazolone mixture with 2-Methyl- 3(2H)-isothiazolone (3:1)</b> INDEX 613-167-00-5	$0 < x < 0,00149$	<b>Acute Tox. 2 H310, Acute Tox. 2 H330, Acute Tox. 3 H301, Skin Corr. 1C H314, Eye Dam. 1 H318, Skin Sens. 1A H317, Aquatic Acute 1 H400 M=100, Aquatic Chronic 1 H410 M=100, EUH071</b> <b>Skin Irrit. 2 H315: <math>\geq 0,06\%</math> - <math>&lt; 0,6\%</math>, Skin Sens. 1A H317: <math>\geq 0,0015\%</math>, Eye Dam. 1 H318: <math>\geq 0,6\%</math>, Eye Irrit. 2 H319: <math>\geq 0,06\%</math> - <math>&lt; 0,6\%</math></b> <b>ATE Oral: 100 mg/kg, ATE Dermal: 50,001 mg/kg, ATE Inhalation vapours: 0,501 mg/l, ATE Inhalation mists/powders: 0,051 mg/l</b>
EC CAS 55965-84-9		

The full wording of hazard (H) phrases is given in section 16 of the sheet.

### SECTION 4. First aid measures

#### 4.1. Description of first aid measures

No effects requiring implementation of special first aid measures are expected. The following information represents practical indications of correct behaviour in the event of contact with a chemical product, even if not hazardous.

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice. Avoid further contact with contaminated clothing.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. Get medical advice/attention.

#### Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

#### 4.2. Most important symptoms and effects, both acute and delayed



# VITEX S.A.

## ACRYLIC PRIMER

Revision nr.8  
Dated 02/07/2024  
Printed on 02/09/2024  
Page n. 3 / 10  
Replaced revision:7 (Dated 10/05/2022)

EN

### SECTION 4. First aid measures ... / >>

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

#### 4.3. Indication of any immediate medical attention and special treatment needed

If skin irritation or rash occurs: Get medical advice / attention.

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

### SECTION 5. Firefighting measures

#### 5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

#### 5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

#### 5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

### SECTION 6. Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

#### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

#### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

#### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

### SECTION 7. Handling and storage

#### 7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.



# VITEX S.A.

## ACRYLIC PRIMER

Revision nr.8  
 Dated 02/07/2024  
 Printed on 02/09/2024  
 Page n. 4 / 10  
 Replaced revision:7 (Dated 10/05/2022)

EN

### SECTION 7. Handling and storage ... / >>

#### 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

#### 7.3. Specific end use(s)

Information not available

### SECTION 8. Exposure controls/personal protection

#### 8.1. Control parameters

Information not available

#### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

##### HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability time. The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

##### SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

##### EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

##### RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

##### ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

### SECTION 9. Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	viscous liquid	
Colour	transparent white	
Odour	characteristic	
Melting point / freezing point	not available	
Initial boiling point	not available	
Flammability	not available	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	> 93 °C	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
pH	8-9	
Kinematic viscosity	not available	
Dynamic viscosity	65-75 KU	Method:ASTM D 562 Temperature: = 25 °C
Solubility	not available	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	
Density and/or relative density	1,01-1,05 kg/l	Method:ISO 2811
Relative vapour density	not available	
Particle characteristics	not applicable	



# VITEX S.A.

## ACRYLIC PRIMER

Revision nr.8  
Dated 02/07/2024  
Printed on 02/09/2024  
Page n. 5 / 10  
Replaced revision:7 (Dated 10/05/2022)

EN

### SECTION 9. Physical and chemical properties ... / >>

#### 9.2. Other information

##### 9.2.1. Information with regard to physical hazard classes

Information not available

##### 9.2.2. Other safety characteristics

Information not available

### SECTION 10. Stability and reactivity

#### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

#### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

#### 10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

#### 10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

#### 10.5. Incompatible materials

Information not available

#### 10.6. Hazardous decomposition products

Information not available

### SECTION 11. Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Metabolism, toxicokinetics, mechanism of action and other information

Information not available

##### Information on likely routes of exposure

Information not available

##### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

##### Interactive effects

Information not available

##### ACUTE TOXICITY

ATE (Inhalation) of the mixture:	Not classified (no significant component)
ATE (Oral) of the mixture:	Not classified (no significant component)
ATE (Dermal) of the mixture:	Not classified (no significant component)

1,2-benzisothiazol-3(2H)-one	
LD50 (Dermal):	> 1,221 mg/kg 1,2-benzisothiazolin-3-one
LD50 (Oral):	> 2,175 mg/kg 1,2-benzisothiazolin-3-one
LC50 (Inhalation vapours):	0,5 mg/l

##### SKIN CORROSION / IRRITATION



# VITEX S.A.

## ACRYLIC PRIMER

Revision nr.8  
Dated 02/07/2024  
Printed on 02/09/2024  
Page n. 6 / 10  
Replaced revision:7 (Dated 10/05/2022)

EN

### SECTION 11. Toxicological information ... / >>

Does not meet the classification criteria for this hazard class

#### SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

#### RESPIRATORY OR SKIN SENSITISATION

May produce an allergic reaction.

Contains:

5-Chloro-2-methyl- 3(2H)-isothiazolone mixture with 2-Methyl- 3(2H)-isothiazolone (3:1)

2-methyl-2H-isothiazol-3-one

1,2-benzisothiazol-3(2H)-one

#### GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

#### CARCINOGENICITY

Does not meet the classification criteria for this hazard class

#### REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

#### STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

#### STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

#### ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

#### 11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

### SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

#### 12.1. Toxicity

5-Chloro-2-methyl- 3(2H)-isothiazolone mixture with 2-Methyl- 3(2H)-isothiazolone (3:1)

EC50 - for Crustacea > 0,018 mg/l/48h

Chronic NOEC for Fish 0,5 mg/l

1,2-benzisothiazol-3(2H)-one

LC50 - for Fish > 2,18 mg/l/96h 1,2-benziosothiazolin-3-one Oncorhynchus mykiss OECD Test Guideline 203

EC50 - for Crustacea > 2,94 mg/l/48h 1,2-benziosothiazolin-3-one Daphnia magna OECD Test Guideline 202

EC50 - for Algae / Aquatic Plants > 0,11 mg/l/72h 1,2-benziosothiazolin-3-one Pseudokirchneriella subcapitata OECD Test Guideline 201

#### 12.2. Persistence and degradability

Information not available

#### 12.3. Bioaccumulative potential



# VITEX S.A.

## ACRYLIC PRIMER

Revision nr.8  
Dated 02/07/2024  
Printed on 02/09/2024  
Page n. 7 / 10  
Replaced revision:7 (Dated 10/05/2022)

EN

### SECTION 12. Ecological information ... / >>

2-methyl-2H-isothiazol-3-one  
Partition coefficient: n-octanol/water 0,32 Log Kow

#### 12.4. Mobility in soil

Information not available

#### 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

#### 12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

#### 12.7. Other adverse effects

Information not available

### SECTION 13. Disposal considerations

#### 13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.  
Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.  
CONTAMINATED PACKAGING  
Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

### SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

#### 14.1. UN number or ID number

not applicable

#### 14.2. UN proper shipping name

not applicable

#### 14.3. Transport hazard class(es)

not applicable

#### 14.4. Packing group

not applicable

#### 14.5. Environmental hazards

not applicable

#### 14.6. Special precautions for user

not applicable

#### 14.7. Maritime transport in bulk according to IMO instruments

Information not relevant



# VITEX S.A.

## ACRYLIC PRIMER

Revision nr.8  
Dated 02/07/2024  
Printed on 02/09/2024  
Page n. 8 / 10  
Replaced revision:7 (Dated 10/05/2022)

EN

### SECTION 15. Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Contained substance

Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors  
not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage  $\geq$  than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Information not available

VOC (Directive 2004/42/EC) :

Primers.

#### 15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

### SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>Acute Tox. 2</b>	Acute toxicity, category 2
<b>Acute Tox. 3</b>	Acute toxicity, category 3
<b>Acute Tox. 4</b>	Acute toxicity, category 4
<b>Skin Corr. 1B</b>	Skin corrosion, category 1B
<b>Skin Corr. 1C</b>	Skin corrosion, category 1C
<b>Eye Dam. 1</b>	Serious eye damage, category 1
<b>Eye Irrit. 2</b>	Eye irritation, category 2
<b>Skin Irrit. 2</b>	Skin irritation, category 2
<b>Skin Sens. 1A</b>	Skin sensitization, category 1A
<b>Aquatic Acute 1</b>	Hazardous to the aquatic environment, acute toxicity, category 1
<b>Aquatic Chronic 1</b>	Hazardous to the aquatic environment, chronic toxicity, category 1
<b>H310</b>	Fatal in contact with skin.
<b>H330</b>	Fatal if inhaled.
<b>H301</b>	Toxic if swallowed.
<b>H311</b>	Toxic in contact with skin.
<b>H302</b>	Harmful if swallowed.
<b>H314</b>	Causes severe skin burns and eye damage.
<b>H318</b>	Causes serious eye damage.
<b>H319</b>	Causes serious eye irritation.
<b>H315</b>	Causes skin irritation.
<b>H317</b>	May cause an allergic skin reaction.
<b>H400</b>	Very toxic to aquatic life.
<b>H410</b>	Very toxic to aquatic life with long lasting effects.
<b>EUH071</b>	Corrosive to the respiratory tract.
<b>EUH210</b>	Safety data sheet available on request.





# VITEX S.A.

## ACRYLIC PRIMER

Revision nr.8  
Dated 02/07/2024  
Printed on 02/09/2024  
Page n. 9 / 10  
Replaced revision:7 (Dated 10/05/2022)

EN

### SECTION 16. Other information ... / >>

#### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

#### GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
  2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
  3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
  4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
  5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
  6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
  7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
  8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
  9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
  10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
  11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
  12. Regulation (EU) 2016/1179 (IX Atp. CLP)
  13. Regulation (EU) 2017/776 (X Atp. CLP)
  14. Regulation (EU) 2018/669 (XI Atp. CLP)
  15. Regulation (EU) 2019/521 (XII Atp. CLP)
  16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
  17. Regulation (EU) 2019/1148
  18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
  19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
  20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
  21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
  22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
  23. Delegated Regulation (UE) 2023/707
  24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
  24. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)
- The Merck Index. - 10th Edition
  - Handling Chemical Safety
  - INRS - Fiche Toxicologique (toxicological sheet)
  - Patty - Industrial Hygiene and Toxicology
  - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
  - IFA GESTIS website
  - ECHA website
  - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy



# VITEX S.A.

## ACRYLIC PRIMER

Revision nr.8  
Dated 02/07/2024  
Printed on 02/09/2024  
Page n. 10 / 10  
Replaced revision:7 (Dated 10/05/2022)

EN

### SECTION 16. Other information ... / >>

#### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

#### CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

#### Changes to previous review:

The following sections were modified:

03 / 04 / 08 / 09 / 11 / 12 / 16.