

CIMENTOL

Acrylic Paint For Concrete Surfaces, Solvent-based

Excellent solvent-based acrylic masonry paint, suitable for application on concrete floor surfaces, garage, walls, tiles and sport courts, ideal for interior and exterior use. It offers great durability against adverse weather conditions and atmospheric pollution. It provides strong adhesion, great hiding power and hardness.



Advantages:

- Great durability under adverse weather conditions and atmospheric pollution
- Strong adhesion and high hardness on walls, concrete floors, tiles, garages, tennis courts, etc

PRODUCT FEATURES

TECHNICAL CHARACTERISTICS

Viscosity

90 ± 10 KU (ASTM D 562, 25°C)



Density

1,40 ± 0,02 Kg / L (ISO 2811) for white

Gloss

< 30 units @ 60° (ISO 2813)

FINISH

Mat	Satin	Gloss
	✓	
Satin Finish		

DILUTION



Up to 5%

- For brushing with Brush Solvent T-300
- For spraying with Spray Gun Solvent T-350

COLOURS

White, Yellow, Ochre, Grain, Red terracota, GreenTennis, Blue, Coal, Carbon



COVERAGE



One coat

10-12 m²/L

Two coats

5-6 m²/L

DRYING TIME




Touch dry

20-40 min

Recoat

6-8 h

COLOR CARDS - FANDECKS



PACKAGING

White	750 mL	2.5 L
Shades	750 mL	2.5 L



EXTERIOR USE – CEMENT PAINTS

APPLICATION

APPLICATION FIELD

For any cement surface.

PREPARATION



Surfaces should be smooth, clean and dry, free from grease, dust, loose or flaking paint.



Cimentol is applied directly to concrete without any primer.



High absorbing or loose surfaces should be primed with Durovit.



BHMATA

1

Dilute up to 5% for brushing with brush solvent T-300 or for spraying with spray gun solvent T-350 and stir well before use.

2

Apply the first coat by brush, roller or spray gun.

3

Recoat after 6-8 hours.

TIPS

- Application at 5-35°C and <70% RH. Don't apply if there is a risk of rain/frost in the next 48 hours.
- Allow new concrete surfaces to cure a minimum of 30 days prior to paint application.
- Apply it outdoor or in a well-ventilated area.

- Clean rollers, brushes with Brush Solvent T-300 and then with soapy water or detergent. Use Spray Gun Solvent T-350 to clean spray guns.
- Minimize paint wastage by estimating how much paint you will need.
- Recover unused paint for re-use. After paint application, seal the container and

store it for future use.

- Do not dispose of liquid waste into ground water table. Unused paint requires special handling for safe disposal.

ADDITIONAL INFORMATION

VOCs (Volatile Organic Compounds)



"Exterior walls of mineral substrate" VOC content limit **430 g/L**. Maximum VOC content **428 g/L** VOCs (ready for use product).

PRECAUTIONS



Please read carefully the labelling mentioned on the can before use. For detailed instructions on hazards and safety in use the Safety Data Sheet is available upon request. Poisons Control Centre Tel. : +30 210 7793 777

STORAGE



5°C-38°C

Keep containers closed in a cool and dry area.

The above technical data, information and instructions are based on our long experience and laboratory tests and are intended only to describe the product and determine its application. However, the end user should check the suitability of the product for its intended use. Our company guarantees the quality of the product itself, and in any case bears no responsibility for any damage or damage caused if the product is not used properly and in accordance with its instructions for use. The company has the right to revise this technical data sheet without any prior notice.

+30.210.5589.400
TECHNICAL SUPPORT

ISO 9001
14001
CERTIFIED 45001

